

CLAI ND

N₂ PICO



“The modular and long life solution for all process plants”

Nitrogen generator



MODELS

N₂ Pico 3

N₂Pico 4

N₂ Pico 5

N₂ Pico 6



TECHNICAL ADVANTAGES

- **Excellent efficiency:** the air consumption is minimised thanks to the FAST PURITY® system. The enhanced efficiency allows to reach a high level of nitrogen purity
- **Oxygen analyser and Pressure regulator:** are included as standard in all the nitrogen generators.
- **No buffer:** the N₂ FLO, PICO & MAXI generators only need one vessel, used both as a buffer and as a consumption nitrogen reservoir
- **Easy and fast installation:** thanks to the electronic control with pre-set programs

FEATURES

- **Safety:** the generator can work unattended and independently 24 hours a day, 365 days a year without requiring surveillance or programming
- **Automatic stand-by:** if the production flow exceeds the consumption, the generator enters a stand-by mode to reduce energy consumption
- **Oxygen analyser:** included in every N₂ FLO, PICO & MAXI generator, to keep the nitrogen purity under control in real time
- **Custom nitrogen purity:** the nitrogen purity can be set according to customer and application requirements

APPLICATIONS

The most common fields of application for these nitrogen generators include:

- Food packaging and bottling of wine, food oils, juices and water
- Chemical and thermal processes
- Laser cutting and welding
- Lead free welding for electronics



TECHNICAL SPECIFICATIONS

MODELS	Outgoing nitrogen flow* [Nm ³ /h]						
Purity	99,999%	99,99%	99,9%	99,5%	99%	98%	97%
N2 PICO 3	1,5	2,5	5,4	8,6	10,4	13,8	16,1
N2 PICO 4	2	3,3	6,9	11,5	15	18,4	20,7
N2 PICO 5	2,3	4,0	9,2	14,4	18,4	23	26,5
N2 PICO 6	3,5	5,0	10,4	17,3	21,9	27,6	31,1
Air/N2 Ratio	6,45	4,80	3,70	2,80	2,65	2,50	2,40

* The flow capacity refers to inlet air nominal conditions: pressure of 8,5 bar, CMS temperature of 20 °C. If the inlet air pressure is different, apply the correction factors reported below.

TECHNOLOGIES EMPLOY	PSA CLAIND
INLET AIR SPECIFICATIONS	<ul style="list-style-type: none"> Air pressure : min 6,5 / max 13 bar Quality: dry, clean, exhalation free. The inlet air must meet the specifications ISO 8573-1, class quality 1.4.1.
NITROGEN OUTLET PRESSURE	Given the pressure P of the inlet air, the pressure of the nitrogen generated is $1 \div 2.5$ bar lower than P, depending on the flow rate of nitrogen supplied
MOISTURE CONTENT AT OUTLET	-50°C Dew Point ATP
ELETTRICAL SUPPLY	230 Vac \pm 10% 50 Hz 115 Vac \pm 10% 60 Hz
POWER RATING	50 W
INDEX OF PROTECTION	IP 20
AVERAGE NOISE	\leq 60 dB (measured at 1 meter from the generator)
OPERATING TEMPERATURE	5 \div 40°C
DIMENSIONS	Height: 138 cm Width: 40 cm Depth: 130 cm
WEIGHT	PICO 3: 230 kg PICO 4: 270 kg PICO 5: 310 kg PICO 6: 350 kg

CERTIFICATIONS

ISO 9001
BUREAU VERITAS
Certification





C L A I N D

Via Regina 24
22016 Tremezzina
Loc. Lenno (CO)
Italy

Tel. +39 0344 56603
Fax +39 0344 56627
Email: info@claind.it
Website: www.claind.eu